



Nuova Distribution USA, LLC

6940 Salashan Parkway, Building A • Ferndale, WA 98248 www.nuovadistribution.com • (p) 360-366-2226 • (f) 360-366-4015

Victoria Arduino Adonis 3 Group Spec Sheet

Water Requirements

- 3/8" dedicated cold water line with shut-off valve and compression fitting.
- Water hardness cannot exceed 3gpg or 50 ppm. If water hardness exceeds 3gpg a water softener must be installed.
- Minimum incoming water flow rate of 35 GPH and maximum line pressure of 70 PSI / 5 BAR.

Water Softening Equipment

- Water Softener Capacity: Single 4400 gpg
- 2. Water Softener Capacity: Double 8800 gpg
- 3. Water Softener Capacity: Triple 13200 gpg
- 4. Water Softener Capacity: Automatic Programmable
- 5. Water Softener Capacity: Manual 4400 gpg

Power Requirements

Volts: 220 (voltage range of 208-240)

Watts: 5000 Amp draw: 23

Receptacle: Nema L6-30 Twist









NSF / ANSI Std.4

The average water consumption of this machine is 6 gallons per day, which represents 196 drinks at 4oz per drink.

Water Softener/Maintenance Calculation

Cartridge Grain Water Hardness Gallon Capacity Gallons of Water Davs Until Cartridge Capacity (grains per gallon) of Cartridge Used per Day Needs to be Replaced


Counter Space Requirements

Height: 25 inches Depth: 23 inches

Width: 44 inches Weight: 285 pounds

Drain Requirements

Open gravity drain of minimum 1.25 inch I.D., within 4 feet of the machine.



Shipping Dimensions & Weight

Height: 31 inches Depth: 27 inches

Width: 47 inches Weight: 295 pounds



I, the customer, understand that these requirements must be in when the installer arrives. Failure to have the site ready will result in additional service and travel charges, and may cause further delays in installation

Will recent in additional convice and have only on they eaded farther delaye in inclanation.		
Customer Name:	Signature:	
Company Name:		
Phone:	Fax:	Email: